

材質	JIS呼称	板厚mm	SWmm	LWmm	Wmm	定尺L×Smm/質量kg/枚				開口率%
						914×1829	1000×2000	1219×2438	1250×2438	
鉄 TYG グレーチング	XG11	4.5	34	135.4	7.0	24.2		43.1		65.2
	XG12	6.0	34	135.4	7.0	32.4		57.7		59.7
	XG13	6.0	34	135.4	9.0	41.6		74.0		50.4
	XG14	8.0	34	135.4	9.0	55.5		98.7		44.0
	XG21	4.5	36	135.4	7.0	22.9		40.7		65.4
	XG22	6.0	36	101.6	7.0	30.6		54.4		59.4
	XG23	6.0	36	101.6	9.0	39.5		70.1		51.2
	XG24	8.0	36	101.6	9.0	52.5		93.3		44.3
鉄 TXS スタンダード	XS31	1.2	12	30.5	1.5	3.95		7.01		76.5
	XS32	1.6	12	30.5	2.0	7.01		12.50		66.9
	XS33	2.3	12	30.5	3.0	15.10		26.80		47.2
	XS41	1.6	22	50.8	2.0	3.81		6.78		83.7
	XS42	2.3	22	50.8	2.5	6.86		12.20		76.6
	XS43	3.2	22	50.8	3.5	13.40		23.80		65.8
	XS53	3.2	25	61.0	4.0	13.50		23.90		68.5
	XS61	2.3	34	76.2	3.0	5.33		9.48		85.0
	XS62	3.2	34	76.2	4.0	9.88		17.60		78.4
	XS63	4.5	34	76.2	5.0	17.40		30.90		69.5
ステンレス	S-5 1.2	1.2	16	32.0	1.2		2.86			84.3
	S-5 1.5	1.5	16	32.0	1.7		5.06			79.1
	S-31	1.2	12	30.5	1.4		4.44			77.3
	S-32	1.5	12	30.5	1.7		6.74			70.9
	S-33	2.0	12	30.5	2.0		10.60			61.9
	S-41	1.5	22	50.8	1.7		3.68			85.3
	S-42	2.0	22	50.8	2.0		5.76			80.6
	S-43	3.0	22	50.8	3.0		13.00	19.30		69.5
	S-61	2.0	34	76.2	2.4		4.48			87.6
	S-62	3.0	34	76.2	3.2		8.96			81.2
	S-63	4.0	34	76.2	4.0		14.90			74.6
	S-21	4.5	36	101.6	6.0		23.80	35.40		68.9
	S-22	6.0	36	101.6	6.0		31.80	47.30		62.8
アルミ	AL-5-1.5	1.5	16	32	1.5		1.53		2.33	80.1
	AL-31	1.2	12	30.5	1.4		1.52		2.32	77.2
	AL-32	1.5	12	30.5	1.5		2.04		3.11	72.5
	AL-33	2.0	12	30.5	2.0		3.62		5.52	62.2
	AL-42	2.0	22	50.8	2.0		1.98		3.01	80.3
	AL-43	3.0	22	50.8	3.0		4.44		6.77	69.4
	AL-63	4.0	34	76.2	4.0		5.12		7.80	74.7