

製品番号	板厚mm	SWmm	LWmm	Wmm	定尺L×Smm/質量kg/枚				開口率%
					914×914	914×1829	1000×1000	1000×2000	
鉄	0.4	1.4	2.0	0.45	○				24.4
	0.5	2.2	3.0	0.55	○				42.7
		3.0	4.6	0.65	○	○			55.0
		3.1	6.0	0.75		○			52.1
		4.0	8.0	0.8		○			64.6
		7.0	14.0	0.8		○			82.3
		0.6	4.0	8.0	0.8		○		61.1
	0.8	4.0	8.0	0.9		○			50.8
		6.5	14.0	1.0		○			69.8
		7.0	14.0	1.0		○			72.6
		10.0	20.0	1.0		○			81.7
		14.0	25.0	1.0		○			87.4
	1.0	6.5	14.0	1.1		○			63.3
		7.0	14.0	1.1		○			66.7
		10.0	20.0	1.1		○			77.5
		14.0	25.0	1.1		○			84.5
	1.2	7.0	14.0	1.3		○			59.2
		10.0	20.0	1.3		○			72.5
ステンレス	0.5	3.0	8.0	0.7				○	53.0
		3.1	6.0	0.7			○		56.1
		4.0	8.0	0.8			○		64.6
		7.0	14.0	1.0				○	79.6
	0.6	3.0	8.0	0.8				○	43.3
		7.0	14.0	0.8				○	79.9
	0.8	7.0	14.0	1.0				○	72.6
		10.0	20.0	0.9				○	82.4
		14.0	25.0	1.0				○	87.4
		16.0	32.0	0.9				○	89.6
	1.0	7.0	14.0	1.0				○	68.2
		10.0	20.0	1.0				○	78.3
16.0		32.0	1.1				○	86.8	
アルミ	0.5	2.0	3.0	0.5				○	31.0
		3.0	4.0	0.7				○	37.0
		3.0	4.6	0.7				○	52.6
		3.1	6.0	0.7				○	54.6
		4.0	8.0	0.8				○	64.6
		7.0	14.0	1.0				○	79.6
	0.8	3.0	4.0	0.8				○	33.0
		4.0	8.0	0.8				○	54.0
		4.0	8.0	1.0				○	47.0
		7.0	14.0	1.0				○	72.6
		10.0	20.0	1.0				○	81.7
	1.0	14.0	25.0	1.0				○	87.4
		7.0	14.0	1.0				○	68.2
		10.0	20.0	1.0				○	78.3
1.5	14.0	25.0	1.0				○	74.0	
	15.0	32.0	1.5				○	77.0	